

Specifications

Nominal Tons	Power Supply V-ph-Hz	Rated Current	Capacity BTU	Performance Air Flow / Noise	Liquid Pipe	Gas Pipe
1.5	208-230/1/60	6.65 A	17500	1500 CFM / 62 DB (A)	3/8"	3/4"
2.0	208-230/1/60	8.75 A	23000	1580 CFM / 62 DB (A)	3/8"	3/4"
2.5	208-230/1/60	11.95 A	30000	3000 CFM / 62 DB (A)	3/8"	3/4"
3.0	208-230/1/60	20 A	35000	3250 CFM / 65 DB (A)	3/8"	7/8"
3.5	208-230/1/60	22.1 A	42000	4200 CFM / 65 DB (A)	3/8"	7/8"
4.0	208-230/1/60	24.3 A	48000	4400 CFM / 65 DB (A)	3/8"	1 1/8"
5.0	208-230/1/60	29.4 A	57500	4250 CFM / 65 DB (A)	3/8"	1 1/8"

R410A environmentally friendly refrigerant

Condenser Cabinet Dimensions (W x H x D) & Weight (lbs.)



1.5	21 7/8" x 24 3/4" x 21 7/8"	119 Lbs.
2.0	23 5/8" x 24 3/4" x 23 5/8"	128 Lbs.
2.5	28" x 24 3/4" x 28"	156 Lbs.
3.0	29 1/8" x 24 3/4" x 29 1/8"	161 Lbs.
3.5	28" x 29 1/2" x 28"	191 Lbs.
4.0	28" x 32 5/8" x 28"	200 Lbs.
5.0	29 1/8" x 32 5/8" x 29 1/8"	213 Lbs.

