

Specifications

Nominal Tons	Power Supply V-ph-Hz	Rated Current	Capacity BTU	Performance Air Flow / Noise	Liquid Pipe	Gas Pipe
1.5	208-230/1/60	1.5 A	18000	650 CFM / 45 DB (A)	3/8"	3/4"
2.0	208-230/1/60	1.5 A	22400	800 CFM / 48 DB (A)	3/8"	3/4"
2.5	208-230/1/60	2.0 A	29000	950 CFM / 53 DB (A)	3/8"	3/4"
3.0	208-230/1/60	2.0 A	36000	1350CFM / 53 DB (A)	3/8"	7/8"
3.5	208-230/1/60	2.0 A	42000	1350CFM / 55 DB (A)	3/8"	7/8"
4.0	208-230/1/60	2.0 A	48000	1600CFM / 55 DB (A)	3/8"	1 1/8"
5.0	208-230/1/60	3.0 A	57000	1960CFM / 58 DB (A)	3/8"	1 1/8"

Air Handler Cabinet Dimensions (W x H x D) & Weight (lbs.)

1.5	18 1/8" x 41 3/8" x 20 1/2"	114 Lbs.
2.0	18 1/8" x 41 3/8" x 20 1/2"	114 Lbs.
2.5	18 1/8" x 41 3/8" x 20 1/2"	125 Lbs.
3.0	19 5/8" x 46 1/2" x 20 5/8"	139 Lbs.
3.5	19 5/8" x 46 1/2" x 20 5/8"	143 Lbs.
4.0	22" x 54 1/2" x 24"	178 Lbs.
5.0	22" x 54 1/2" x 24"	187 Lbs.

Optional Electric Heat Kits

1.5 ton – 2.5 ton
5kw, 7.5kw, 10kw

3.0 ton – 5.0 ton
5kw, 7.5kw, 15kw, 20kw

